

Order No.: 5XC1A41B08DB | GTIN (EAN): 4058352216729


Product description: SL11mc,ST1.2a,2870lm740,Plus



Streetlight 11 micro LED, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, silver coated, highly specular, primary optical cover: cover, of PMMA, transparent, light distribution: ST1.2a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, side-entry, LED LED High Power, luminous flux: 2.870 lm, light colour: 740, colour temperature: 4000K, control gear: ECG Plus, control: optimised constant luminous flux control (CLO 2.0), overheat protection, power reduction, digital communication interface, time-dependent luminous flux control, flexible luminous flux parameterisation, electronic power reduction, with cable H07RN-F 5x 1.5mm², mains connection: 220..240V, AC, 50/60Hz, connection cable pre-assembled, cable length: 6,5 m, start of lifetime: 24 W, end of lifetime: 25 W, reduction: 11 W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 600 mm, width: 174 mm, height: 116mm, spigot size: 60/76mm (post-top) and 42/60mm (side-entry), mast flange for spigot size: 42mm: 5XC10008XM4, 60mm: 5XC10008XM2, 76mm: 5XC10008XM1, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, impact resistance: IK09, permissible ambient temperature for outdoor applications: -25..+50°C, standard-compliant lighting for roads and squares, packaging unit: 1 piece

4058352216729
5XC1A41B08DB

LED 4000K / CRI ≥ 70 Φ_h 2870 lm



Lamps: LED
Wt. (kg): 5.2
GTIN (EAN): 4058352216729

siteco 5XC1A41B08DB

The luminaire contains built-in LED lamps

A++
A+
A
B
C
D
E

}

LED

The LED-lamps cannot be changed in the luminaire

874/2012

